


Ai-logger 1000



Smart

Smart zero export control design

Simple

Easy to install on site

Reliable

Adapt to various application scenarios

Technical Specification	Ai-logger 1000
Device Management	
Max. Number of Manageable Devices	80
Communication Interface	
North Communication	
WLAN	WAN x 1, 2.4GHz
LAN	LAN x 1, 10 / 100 / 1000 Mbps
2G / 3G / 4G	Option, Only for China market
South Communication	
RS485	COM x 3, 1000 m
Ethernet	1
PLC	1,Option , Only for China market
others	
Digital / Analog Input / Output	DI x 4, DO x 2
Interaction	
LED	LED Indicator x 4 – COM 1~3, North communication
WEB	Embedded Web
USB	USB 2.0 x 1
APP	Solplanet APP
RST	1
Environment	
Operating Temperature Range	-40°C ~ 60°C (-40°F ~ 140°F)
Storage Temperature	-40°C ~ 70°C (-40°F ~ 158°F)
Relative Humidity (Non-condensing)	5% ~ 95%
Max. Operating Altitude	4,000 m (13,123 ft.)
Electrical	
DC Power Supply	12V / 2A
Power Consumption	Typical 8 W, Max. 15 W
Mechanical	
Dimensions (W x H x D)	240mm×126mm×42mm
Weight	2 kg
Protection Degree	IP20
Installation Options	Wall Mounting, DIN Rail Mounting, Tabletop Mounting

Primary Version, for reference only.2022-07
All rights reserved by AISWEI. The right to make changes to this material without notice is reserved.
This information does not serve as an explicit commitment or implication of technical indicators.